

# Control4® 4-Zone and 8-Zone Power Amplifiers



## Control4® 4-Zone Power Amplifier C4-AMP104 Control4® 8-Zone Power Amplifier C4-AMP108

Control4® 100 Series Power Amplifiers deliver high-quality audio to four or eight stereo zones. Regardless of the size of your home or project, you'll enjoy lots of power for your multi-room audio system.

- 4 and 8-Zone Power Amplifiers let you enjoy up to 55 watts of high-quality sound in each zone
- Bridgeable outputs provide up to 200 watts, delivering more power for larger speakers or outdoor zones
- Energy saving design allows the amplifier to go into standby when not in use
- Automatic fault detection and system reset protects the amplifier and connected speakers from damage
- Rack mount kit included (3U Rack Height)



4-Zone Power Amplifier



8-Zone Power Amplifier

## Control4® 4-Zone and 8-Zone Power Amplifiers

	Control4 4-Zone Power Amplifier	Control4 8-Zone Power Amplifier
Model Number	C4-AMP104	C4-AMP108
Zone Line Inputs	4 Stereo, RCA Style	8 Stereo, RCA Style
Zone Speaker Outputs	4 Stereo, Phoenix Style	8 Stereo, Phoenix Style
Zone Line Outputs	4 Stereo, RCA Style	8 Stereo, RCA Style
Global Line Input	1 Stereo, RCA Style	1 Stereo, RCA Style
Global Line Output	1 Stereo, RCA Style	1 Stereo, RCA Style
Rated Wattage Per Channel (Two Channels Driven)	55W @ 8 Ohms 100W @ 4 Ohms	55W @ 8 Ohms 100W @ 4 Ohms
Rated Wattage Per Channel (All Channels Driven)	45W @ 8 Ohms 60W @ 4 Ohms	30W @ 8 Ohms 40W @ 4 Ohms
Rated Wattage (Bridged)	200W @ 8 Ohms	200W @ 8 Ohms
Frequency Response	20Hz - 40kHz (+/- 3dB)	20Hz - 40kHz (+/- 3dB)
Signal-to-Noise Ratio	>-86 dB A-Weighted	>-86dB A-Weighted
THD	<0.3% at 1 kHz	<0.3% at 1 kHz
Zone Input Gain	Yes	Yes
Global Input Gain	Yes	Yes
Voltage Input Trigger	5 - 30V AC or DC	5 - 30V AC or DC
Voltage Output Trigger	5 - 30V AC or DC	5 - 30V AC or DC
Rack Mount Kit	Included—3U Vented	Included—3U Vented
Power Requirements	100-240VAC, 50-60 Hz	100-240VAC, 50-60 Hz
<b>Environmental</b>		
Operational Temperature	32° F - 104° F (0° C - 40° C)	32° F - 104° F (0° C - 40° C)
Humidity	5% to 95% Non-Condensing	5% to 95% Non-Condensing
Storage	-4° F - 158° F (-20° C - 70° C)	-4° F - 158° F (-20° C - 70° C)
<b>Miscellaneous</b>		
Dimensions Without Rack Mount Kit (H×W×D)	2U 17.32" × 3.43" × 9.69" (440mm × 87mm × 246mm)	2U 17.32" × 3.43" × 9.69" (440mm × 87mm × 246mm)
Dimensions With Rack Mount Kit (H×W×D)	3U 20.79" × 5.39" × 9.69" (528mm × 137mm × 246mm)	3U 20.79" × 5.39" × 9.69" (528mm × 137mm × 246mm)
Weight	11 lbs (4.99 kg)	13.2 lbs (5.99 kg)

